

# PORTABLE OXYGEN CONCENTRATOR

## ZEN-O LITE™

Part No	Weight	Purity	Max Oxygen Discharge Pressure	Operating Altitude	Operating Temperature	Power Requirements
RS-00608-AUS-D (2x Battery)	2.5 kg	87- 96%	20.5 psi	0' to 13,000' (0m to 4,000m)	5°C and 40°C	100-240V AC (± 10%) 50-60Hz in, 24V DC, 5.0A out

- Zen-O lite™ delivers up to 1050 ml of oxygen per minute in pulse mode and is adjustable in 0.5 increments up to setting 5. Zen-O lite™ automatically adjusts the amount of oxygen delivered to meet the patient's breath rate
- Zen-O lite™ has easy to understand intuitive buttons and LCD panel for straightforward operation
- The Eco Mode feature allows users to switch the operation of the device from delivery a fixed pulse of oxygen at each inhalation to a fixed volume of oxygen per minute, to allow for longer battery duration
- The Auto Mode feature activates after 60 seconds if no breath is detected, the device will automatically deliver pulses at a rate of 18 breaths per minute to the user. This feature allows users to continue receiving some oxygen if the cannula is dislodged
- Weighing just 2.5kg, Zen-O lite™ can be used in the comfort of a patient's home and is ideal for use outside the home. Zen-O lite™ offers unequalled independence and flexibility to patients that require supplemental oxygen therapy
- Zen-O lite™ is designed with easily replaceable sieve modules. The sieve modules can be swapped in under 5 minutes by either the user or home oxygen provider
- A system indicator flashes each time a breath is detected during use, giving users the assurance that oxygen is being delivered.
- Zen-O lite™ is manufactured in the UK and USA to the exacting standards of the European Medical Directive and United States Food and Drug Administration
- Zen-O lite™ is built to last and is supplied with a 3 year warranty, the battery, sieve modules and other accessories have a 1 year warranty

### Applications:

Zen-O lite™ portable oxygen concentrator offers reliability, flexibility and support active lifestyles of patients requiring oxygen therapy.

Zen-O lite™ features breath sensitivity and Rate Responsive Therapy™ technologies that enables rapid breath detection and oxygen delivery required.

Zen-O lite™ delivers oxygen on demand, which is triggered by the patient's inhalation. Whether a patient is climbing the stairs or taking a walk, Zen-O lite™ will automatically respond to the breath rate by adjusting the amount of oxygen needed to ensure the patient remains saturated. It offers an oxygen output of up to 1050ml per minute and holds one battery that can last up to 4 hours at setting 2.

Spare Parts:	Part Number:
Zen-O lite™ Rechargeable Battery	RS-00601
Zen-O lite™ AC Power Supply	RS-00602
Zen-O lite™ DC Power Supply	RS-00605
Zen-O lite™ Carry Bag	RS-00606
Replacement Sieve Modules	RS-00616
Zen-O lite™ Cannula Wrench	RS-00617
Zen-O lite™ Rucksack	RS-00619
Zen-O lite™ Cannula Filter pk of 10	RS-00512
Accessories Bag	RS-00523

Each Zen-O™ lite device (Part No: RS-00608-AUS-D) is supplied with a carry bag, two batteries and AC/DC power cables.

